



**Electrical Specifications:**

Meets USB2.0 specifications.  
 Current Rating : 1.5 A Max.  
 Insulator resistance : 1000 Megohms min .  
 Contact resistance : 30 m ohm Max.  
 DWV : 500v AC/60s Pin to Pin;1000v AC/60s Pin to shell.  
 Operating Temperature : -40°C TO +85°C

**Material and Finish**

Receptacle Housing : Zn Alloy 3,Nickel Plated  
 Panel Nut : Coper Alloy,Nickel Plated  
 Panel Gasket : Silicone  
 USB OVERMOLD : ABS, Black.  
 USB CONN : USB AF2.0  
 DURABILITY : 1500 Mating Cycles.

Connector can be front mounted to a maximum panel thickness of 3.2mm.

BOM:  
30u" 3353K00030

Panel Cut-Out

RoHS COMPLIANT

設計 DR. Leon 2015/01/06	核准 APPD. Marco 2015/01/06	容許公差 .XXX ±0.10 .XX ±0.25 .X ±0.38 X ±0.50 ANG ±3'	TOLERANCE	品名 ARTICLE 3353防水接頭(盒端加USB)
版本說明 REVISION NOTE ——修正4C尺寸——				圖號 DWG NO. 3353K00030
KINSUN		單位 UNIT 比例 SCALE 張數 SHEET 版本 REV. mm 2/1 1/1 C		