



RECOMMENDED P.C.B LAYOUT
TOP VIEW (COMPONENT SIDE)

- P/N. G/F: 3050605501
 6u": 3050605601
 374C 15u": 3050665701
 15u": 3050605701
 30u": 3050605801
 50u": 3050605901

新增374C(淺綠色)
膠殼

MATERIALS:
 PLASTIC HOUSING: HIGH TEMP. THERMOPLASTIC
 FLAMMABILITY RATING UL 94V-0.
 CONTACTS: PHOSPHOR BRONZE
 PLATING: GOLD PLATING OVER NICKEL IN CONTACT.
 MATTED TIN PLATING OVER NICKEL IN SOLDER AREA.
 SHIELD: BRASS PLATING NICKEL ALLOY.

設計DR. Marco 29/May/2015	核准APPD. Jerry 29/May/2015	容許公差 .XXX ±0.10 .XX ±0.25 .X ±0.38 X ±0.50 ANG ±3°	TOLERANCE	品名 ARTICLE 3050 8P8C SMT FULL SHIELDING
版本說明 REVISION NOTE --- 依E302-1505038 新增374C 規格 ---				圖號 DWG NO. 3050605601
KINSUN				單位 UNIT 比例 SCALE 張數 SHEET 版本 REV. mm 4/1 1/1 H